

## KODAK 605 Photo Printer

# The picture of value.

- Perfect solution for low to mid-volume locations
- Versatile and efficient: three print sizes— maximum ability to fulfill your customer's needs for the most popular print sizes with just one printer and just one media SKU.
- Consumers love prints protected by KODAK XTRALIFE Lamination—delivering stain-resistant, waterproof prints that last a lifetime\*
- Compact size and reduced weight printer
- Direct PC connectivity possible for truly portable printing solution



### Printer Package Contents

KODAK 605 Photo Printer, Power Cord, USB Cable (2 M), Welcome Kit and Print Catch Tray

### Printer Specifications\*\*

Printing process	Thermal dye sublimation
Image quality	300 dpi (continuous tone)
Print speed	11 sec. for 4x6 in. (10x15 cm) <sup>1</sup> 19 sec. for 5x7 in. (13x18 cm) or 6x8 in. (15x20 cm)
Maximum imageable area	4x6 in. (10x15 cm) borderless 6x8 in. (15x20 cm) borderless
Media capacity	750 4x6 in. (10x15 cm) prints 375 5x7 in. (13x18 cm) prints 375 6x8 in. (15x20 cm) prints <sup>2</sup>

### Physical Characteristics

Dimensions (Height x Width x Depth)	12.8 x 11.4 x 19.6 in. (33 x 29 x 50 cm)
Weight (without ribbon or paper)	40 lb. (18 kg)

### Computer Information & Software Requirements

Computer interface	<ul style="list-style-type: none"><li>• USB 2.0 and USB 1.1</li><li>• KODAK-provided printer drivers and software</li></ul>
System requirements	<ul style="list-style-type: none"><li>• MICROSOFT WINDOWS 7, WINDOWS 8, WINDOWS XP, XP Professional x64, 2003 Server, or VISTA 32 bit and 64 bit Operating Systems</li><li>• Minimum 1.0 GHz CELERON Microprocessor</li><li>• Minimum 128 MB of RAM<sup>3</sup></li><li>• Minimum 2 GB of available hard disk space<sup>3</sup></li></ul>
Printer drivers and software	WINDOWS 7, WINDOWS 8, WINDOWS XP OS, WINDOWS 2003 Server and WINDOWS VISTA

### Operating Requirements

Power consumption	320 watts maximum
Operating temperature range	+59 to 95F (+15 to 35C)
Relative humidity	20 to 80%

### Regulatory/Compliance

Emissions	FCC Part 15 or equivalent
Safety markings	CCC, CE, EAC, KC, RCM, S UL-AR, UL-C, UL-US

### Ordering Information

CAT No.

KODAK Picture Kiosk G3/G4  
605 Photo Printer Kit

KODAK 605 Photo Printer

4R 4x6 in. (10x15 cm) Print Kit

6R 6x8 in. (15x20 cm) Print Kit

\*Under typical home display conditions.

\*\*Printer specifications are subject to change.

<sup>1</sup>Average 4x6 in. (10x15 cm) print speed of 10 sec. can be achieved using the GR Print Kit

<sup>2</sup>5x7 in. (13x18 cm) print size is on 6x8 in. (15x20 cm) paper

<sup>3</sup>Additional RAM and hard disk space may be needed to support the Operating System installed or the imaging applications being used.

Contact your local Kodak Alaris representative  
for more information, or visit [www.kodakalaris.com](http://www.kodakalaris.com)

© 2015 Kodak Alaris Inc.  
The Kodak and Xtralife trademarks and Kodak trade dress are used under license  
from Eastman Kodak Company.  
12/15

**Kodak** alaris